

Technical data sheet

OKB supply trunking

Item number: 7403811



Ready-to-mount trunking unit for cable routing, consisting of a trunking base with two covers. The scope of delivery contains two lid butt seals and one connector. For height adjustment, six height adjustment units are required. Load capacity up to a maximum of 5 kN. The trunking unit can be supplemented with an adjustable floor covering contact profile for screed limitation in areas of door frames and in front of radiator niches.



St Steel

FS Strip galvanized

Master data

Item number	7403811
Type	OKB E 25085 ON
Description 1	Flushfloor trunking unit
Description 2	blank
Manufacturer	OBO
Dimension	2000x73x85
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	1320 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to-Gate	57,4358 kg CO2e / 1 Meter


Technical data sheet

OKB supply trunking

Item number: 7403811



Dimensions



Length	2,000 mm
Width	210 mm
Height	93 mm
Dimension h	85 mm

Technical data

Mounting opening cover	no
Number of compartments	1 St.
Floor plate	yes
Floor care	Dry
Cover fastening, locking	no
Seal installation option	no
Installation opening for on-floor tank	no
Decouplable	yes
Suitable for expansion joint	no
Mesh wall	no
Minimum screed height	85
With connection opening	no
With equipotential bonding	no
With separating retainer	no
With overhang	yes
Mounting opening	Without
Height-adjustment range, min.	0 mm
Usable cross-section	11000 mm ²
Removable cover	yes
Cross-section, draw a	11008 mm ²
Separating retainer fastening	stecken
Vertical load, large area	to 5,000 N
Vertical load, small area	to 3,000 N
Separating retainer fastening	Plug