

Technical data sheet

UTC3 W with 2 protective contact sockets, white

Item number: 7404610



The ready-for-connection UTC3 universal support has 2 pre-installed 33° protective contact sockets in white of 16 A and one blanking cover for retroinstallation of an installation device of the Modul 45 or Modul 45connect series. Suitable for VL connection cables and device installation units of nominal size 2, 4, R4, 6 and R7.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI. The ready-for-connection UTC3 universal support has 2 pre-installed 33° protective contact sockets in white with 16 A and one blanking cover for retroinstallation of an installation device of the Modul 45 or Modul 45connect series.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI

PA

Polyamide

Master data		
Item number	7404610	
Type	UTC3 W W2	
Description 1	Universal supportConnectWINSTA	
Description 2	VDE, double white	
Manufacturer	OBO	
Dimension	165x76x45	
Material	Polyamide	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	26.9 kg	
Weight unit	kg/100 pc.	


Technical data sheet

UTC3 W with 2 protective contact sockets, white

Item number: 7404610



Dimensions



Length	175 mm
Width	76 mm
Height	60 mm

Technical data

Connection cable, halogen-free	no
Number of installable devices	3
Version for	Double pure white
Cable length	300 mm
Line cross-section	2.5 mm ²
Plug-in system	WINSTA® MIDI
Plug connector system, system-specific	yes
Circuit	1
System length	165 mm
Surge protection	no