Technical data sheet

Wire cable clamp G

Item number: 5302064

Wire cable clamp, formerly DIN 741, for fastening steel wire tensioning ropes. The bracket of the wire rope clamp must be positioned over the unloaded end of the wire rope loop; the clamping body rests against the load-bearing, continuous section of the wire rope loop. To ensure a secure connection, at least 3 wire cable clamps are required per wire rope loop, spaced at intervals of 1–2 times the clamp width. The hexagonal nuts must be tightened evenly in alternating order and retightened after the rope has been loaded for the first time.

CE

St	Steel
G	Electrogalvanised

Master data

Item number	5302064
Type	947 6 G
Description 1	Wire cable clamp
Manufacturer	OBO
Dimension	6mm
Material	Steel
Surface	Electrogalvanised
Surface standard	EN ISO 19598 / EN ISO 4042
Smallest sales unit	25
Unit of quantity	Piece
Weight	1.7 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,0469 kg CO2e / 1 Piece

Technical data sheet

Wire cable clamp G

Item number: 5302064

Dimensions



Dimension A	28 mm
Dimension B	8 mm
Dimension C	5 mm

Technical data

Version for	Not insulated
for cable diameter, min.	6 mm
ROHS-conformant	yes