

# Technical data sheet

Clamp clip 2056 N-foot, 1-fold, plastic pressure sleeve, Al

Item number: 1187338



Clamp clip with N-foot, plastic pressure sleeve made of polypropylene. For vertical and horizontal mounting of 1 single cable on a C-profile rail. For slot width 11–12 mm With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. We recommend the use of a counter-sleeve.



**Alu** Aluminium

## Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 1187338                  |
| Type                               | BS-N1-K-46 ALU           |
| Description 1                      | Clamp clip 2056          |
| Manufacturer                       | OBO                      |
| Dimension                          | 40-46mm                  |
| Material                           | Aluminium                |
| Smallest sales unit                | 50                       |
| Unit of quantity                   | Piece                    |
| Weight                             | 2.55 kg                  |
| Weight unit                        | kg/100 pc.               |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,4138 kg CO2e / 1 Piece |


# Technical data sheet

Clamp clip 2056 N-foot, 1-fold, plastic pressure sleeve, Al

Item number: 1187338



## Dimensions



|                  |       |
|------------------|-------|
| Length           | 25 mm |
| Width            | 51 mm |
| Height           | 73 mm |
| Plate thickness  | 2 mm  |
| Dimension A      | 25 mm |
| Dimension B      | 51 mm |
| Dimension C      | 40 mm |
| Dimension G (mm) | M8    |
| Dimension H      | 73 mm |
| Dimension L      | 45 mm |
| Dimension t      | 2 mm  |

## Technical data

|                                                |               |
|------------------------------------------------|---------------|
| Number of cables/pipes                         | 1             |
| For pipe diameter, max.                        | 46 mm         |
| For pipe diameter, min.                        | 40 mm         |
| for rail with slot width (with interval), max. | 12 mm         |
| for rail with slot width (with interval), min. | 11 mm         |
| Thread                                         | M8            |
| Halogen-free                                   | yes           |
| Length of external dimensions                  | 40 mm         |
| Max. Tightening torque                         | 2 Nm          |
| With plastic trough                            | yes           |
| Mounting type                                  | Profile rail  |
| ROHS-conformant                                | yes           |
| Slot width                                     | 10 mm         |
| Clamping range D, max.                         | 46 mm         |
| Clamping range D, min.                         | 40 mm         |
| Surface addition                               | Untreated     |
| Material addition                              | Aluminium     |
| With counter-trough                            | no            |
| Material of trough                             | Plastic       |
| Material quality of trough                     | Polypropylene |