

Technical data sheet

Cable routing trunking LE 40, trunking width 60

Item number: 6130060



LE cable routing trunking for covered cable routing in internal areas.
Trunking base with base perforation for mounting. Hardly inflammable and self-extinguishing after removal of a naked flame. Change the direction with the fittings and close the trunking ends with end pieces.
Tested to DIN EN 50085-1 and DIN EN 50085-2-1.
Base and cover in set.



PVC Polyvinylchloride

Master data

Item number	6130060
Type	LE 4060 TW rws
Description 1	Cable trunking
Description 2	LE Set 40x60 Sep. 9010
Manufacturer	OBO
Dimension	2000x60x40
Colour	Pure white; RAL 9010
Material	Polyvinylchloride
Smallest sales unit	28
Unit of quantity	Metre
Weight	56.632 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to-Gate	0,9157 kg COe / 1 Meter


Technical data sheet

Cable routing trunking LE 40, trunking width 60

Item number: 6130060



Dimensions



Length	2,000 mm
Width	57 mm
Height	39.1 mm

Technical data

Number of fixed partitions	1
Fastening type	Base perforation
Maintain electrical functions	no
Halogen-free	no
Cable retaining clip	yes
Duct connector	no
Delivery on a roll	no
Usable cross-section	1600 mm ²
ROHS-conformant	yes
Protective film	no
Transparent	no