# Technical data sheet

## Trunking unit, blank, locking, height 100−150 mm

## Item number: 7424500

Ready-to-mount trunking unit with three self-locking blanking covers for cable laying, consisting of the trunking base (floor trough with side and floor covering guide profiles) and trunking lid. Floor trough with holding shackles for self-contacting mounting of dividers. The scope of supply contains six height-adjustable wall fixing brackets, six screed anchors and three cover joint supports (for nominal trunking widths 200 and 300) or three height-adjustable cover joint supports (for nominal trunking widths 400, 500 and 600). Trunking lid screwed down when delivered.

| | |
|---|---|
| St | Steel |
| FS | Strip galvanised |

### Master data

| | |
|---|---|
| Item number | 7424500 |
| Type | OKA-W20010050R |
| Description 1 | Flushfloor trunking unit |
| Description 2 | blank, locking |
| Manufacturer | OBO |
| Dimension | 2400x200x100 |
| Material | Steel |
| Surface | Strip galvanised |
| Surface standard | DIN EN 10346 |
| Smallest sales unit | 2.4 |
| Unit of quantity | Metre |
| Weight | 1075 kg |
| Weight unit | kg/100 m |
| CO2 Footprint (GWP) Cradle-to-Gate | 54,9886 kg CO2e / 1 Meter |

### Dimensions




| | |
|---|---|
| Length | 2,400 mm |
| Width | 200 mm |

# Technical data sheet

## Trunking unit, blank, locking, height 100−150 mm

## Item number: 7424500

### Technical data

| | |
|---|---|
| Mounting opening cover | no |
| Covers | 3 |
| Number of insertable partitions | 1 |
| Number of planned flush-mount units | 3 |
| Number of compartments | 2 St. |
| Mounting system fastening type | Floor |
| Floor plate | yes |
| Cover fastening, locking | yes |
| Seal installation option | yes |
| Installation opening for on-floor tank | no |
| Decouplable | no |
| Suitable for expansion joint | no |
| Mesh wall | no |
| Trunking height, max. | 150 mm |
| Duct height, min. | 100 mm |
| Cover material thickness | 4 |
| Minimum screed height | 100 |
| With connection opening | no |
| With equipotential bonding | no |
| With separating retainer | no |
| With overhang | yes |
| Mounting opening | Without |
| Height-adjustment range, max. | 150 mm |
| Height-adjustment range, min. | 100 mm |
| Removable cover | yes |
| ROHS-conformant | yes |
| Separating retainer fastening | stecken |
| Separating retainer fastening | Plug |