

Technical data sheet

Connector part, 5-pin, black

Item number: 6108964



Connector 5-pin, type WINSTA® MIDI with clamp connection.
Single and multi-wire cables connectable without end sleeve. Not mounted with strain relief and terminable in situ. 250 V, 25 A.

Nominal cross-section: 4 mm²
Stripping length: 55 mm
Insulation removal length: 9 mm



PA Polyamide

Master data		
Item number	6108964	
Type	ST-WIN 5P SW	
Description 1	Plug section	
Description 2	5pole, WINSTA	
Manufacturer	OBO	
Dimension	76x55x17	
Colour	Black	
Material	Polyamide	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	2.97 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to-Gate	0,1257 kg CO2e / 1 Piece	


Technical data sheet

Connector part, 5-pin, black

Item number: 6108964



Dimensions



Length	76 mm
Width	55 mm
Height	17 mm

Technical data

Connection type	Spring balancer connection
Connection cross-section (single-wire), max.	4 mm ²
Connection cross-section (single-wire), min.	0.5 mm ²
Connection cross-section (fine-wire), max.	4 mm ²
Connection cross-section (fine-wire), min.	0.5 mm ²
Type of locking	Integrated in plug connector
Version of the device connection	Connector
Rated surge voltage	6
Fire load	0.17
Built-in variants	Installation part/plug connection
Halogen-free	yes
Contact material	CuSn
Mechanical encoding	yes
Nominal voltage	250 V
Nominal current	25 A
Surface treatment of the contacts	Miscellaneous
Pin labelling	L, N, PE, 1, 2
Pole number	5
ROHS-conformant	yes
Protection rating	IP20
Direction of insertion	Straight
Plug-in system	WINSTA® MIDI
Degree of soiling	3