

Technical data sheet

UTC3 W with 2 protective contact sockets, white

Item number: 7404610



The ready-for-connection UTC3 universal support has 2 pre-installed 33° protective contact sockets in white of 16 A and one blanking cover for reinstallation of an installation device of the Modul 45 or Modul 45connect series. Suitable for VL connection cables and device installation units of nominal size 2, 4, R4, 6 and R7.



PVC connection cable with connector, 3-pin, type WINSTA® MIDI.



PA Polyamide

Master data		
Item number	7404610	
Type	UTC3 W W2	
Description 1	Universal supportConnectWINSTA	
Description 2	double white	
Manufacturer	OBO	
Dimension	165x76x45	
Material	Polyamide	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	26.9 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to-Gate	0,918 kg CO2e / 1 Piece	

Technical data sheet

UTC3 W with 2 protective contact sockets, white


Item number: 7404610



Dimensions



Length	175 mm
Width	76 mm
Height	60 mm



Technical data

Connection cable, halogen-free	no
Number of installable devices	3
Version for	Double pure white
Cable length	300 mm
Line cross-section	2.5 mm ²
ROHS-conformant	yes
Plug-in system	WINSTA® MIDI
Plug connector system, system-specific	yes
Circuit	1
System length	165 mm
Surge protection	no