# Technical data sheet

## UTC4 W with 2+2 protective contact sockets

## Item number: 7404616

The ready-for-connection UTC4 universal support possesses 2 pre-installed 33° protective contact sockets in white and 2 pre-installed 33° protective contact sockets in orange, 250 V~, 16 A. Suitable for VL connection cables and device installation units of nominal size R7, R9 and 9.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI.

PA Polyamide

### Master data

| | |
|---|---|
| Item number | 7404616 |
| Type | UTC4 W W2OR2 |
| Description 1 | Universal supportConnectWINSTA |
| Description 2 | double white,double orange |
| Manufacturer | OBO |
| Dimension | 208x76x45 |
| Material | Polyamide |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 46.1 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to-Gate | 1,2683 kg CO2e / 1 Piece |

# Technical data sheet

## UTC4 W with 2+2 protective contact sockets

## Item number: 7404616

### Dimensions







| | |
|---|---|
| Length | 218 mm |
| Width | 76 mm |
| Height | 60 mm |

### Technical data

| | |
|---|---|
| Connection cable, halogen-free | no |
| Number of installable devices | 4 |
| Version for | Double pure white/double pure orange |
| Cable length | 300 mm |
| Line cross-section | 2.5 mm² |
| ROHS-conformant | yes |
| Plug-in system | WINSTA® MIDI |
| Plug connector system, system-specific | yes |
| Circuit | 2 |
| System length | 208 mm |
| Surge protection | no |